

What is claimed is:

1. A motor vehicle designed to carry a fold-up warning triangle which can be removed from the vehicle, the vehicle comprising:

an opening having a boundary edge and covered by a hatch, said hatch being arranged so that it can move between a closed position and an open position; and

wherein said warning triangle in the folded-up position is secured in an edge portion of said hatch bearing against the boundary edge of the opening in the closed position of said hatch such that a warning surface of said warning triangle is visible to other traffic when said hatch is in its open position.

2. The motor vehicle according to claim 1 wherein said warning surface is situated on one of three legs of said warning triangle.

3. The motor vehicle according to claim 1 wherein said folded-up warning triangle is releasably fitted in a recess in said edge portion of said hatch, said recess having a wall interrupted by at least one hole through which said warning surface is visible to other traffic when said hatch is in its open position.

4. The motor vehicle according to claim 3 wherein said hole is triangle-shaped as a symbolic representation of the shape of said warning triangle in its deployed position.

5. The motor vehicle according to claim 3 wherein said wall of said recess is interrupted by a number of holes arranged alongside each other.

6. The motor vehicle according to claim 3 wherein said wall plane of said recess is interrupted by three holes arranged alongside each other.

7. The motor vehicle according to claim 1 wherein said warning surface is oriented essentially at right angles to a road surface used by the vehicle when said hatch is in its opened position.

8. The motor vehicle according to claim 1 wherein two warning triangles are releasably fitted in respective recesses in said edge portion of said hatch.